



**SITE PLAN**  
SCALE-1:100



**SITE PLAN**  
SCALE-1:100

FIRE SAFETY LEGENDS	
[Symbol]	SLUICE & N.R VALVE
[Symbol]	PUMP WITH MINIMUM PRESSURE 169M AT TERRACE LVL.
[Symbol]	WET RISER CUM DOWN COMER
[Symbol]	HYDRANT OUTLET
[Symbol]	HOSE REEL HOSE
[Symbol]	FIRE CALL POINT
[Symbol]	BOOZER
[Symbol]	FIRE SERVICE INLET
[Symbol]	AREA PROTECTED BY AUTOMATIC DCP EXTINGUISHER
[Symbol]	AREA PROTECTED BY WATER CO2 EXTINGUISHER
[Symbol]	LIGHTNING CONDUCTOR

SPECIFICATION		
SL.NO	NAME	DETAILS
1)	FOUNDATION	R.C.C COLUMN FOOTING RAFT AS PER DESIGN
2)	SUPER STRUCTURE	FIRST CLASS B/W IN CM (1:4) FOR 225mm & CM (1:4) FOR 125 MM
3)	FLOORING	100mm P.C.FLOORING OVER 100mm DRY BEAMED ALDOX OVER 0.075m B/B SOLING OVER LOCAL SAND FILLING
4)	LINTEL	150mm R.C.C LINTEL PROVIDED OVER DOOR & WINDOWS
5)	ROOF	R.C.C ROOF SLAB WITH REQUIRED THICKNESS AS PER STRUCTURAL DESIGN.
6)	TERRACE	PROVIDE 25mm MEDIUM GRA TREATMENT WITH BRICK ON EDGE SOLING OVER LOCAL SAND FILLING FINISHED WITH P.C.C OVER R.C.C TERRACE ROOF FOR HEAT INSULATION & WATER PROOFING.
7)	PLASTER	INNER & OUTER WALL PLASTERED IN CM (1:1:4) & TWO COATS OF WHITE WASH OVER SIDE ONLY

SCHEDULE OF DOOR & WINDOW				
DOOR				
TYPE	WIDTH	HT.	SILL	DESCRIPTION
D1	1.07	2.1	0	WOODEN FLUSH DOOR
D2	0.9	2.1	0	WOODEN FLUSH DOOR
D3	0.92	2.1	0	WOODEN FLUSH DOOR
D4	0.78	2.1	0	WOODEN FLUSH DOOR
WINDOW				
TYPE	WIDTH	HT.	SILL	DESCRIPTION
W0	2.45	1.20	0.9	GLAZED WINDOW
W1	1.5	1.20	0.9	GLAZED WINDOW
W2	1.2	1.20	0.9	GLAZED WINDOW
W3	0.9	1.20	0.9	GLAZED WINDOW
V	0.8	0.6	1.52	GLAZED VENTILATOR

PROPOSED COMMERCIAL CUM RESIDENTIAL BUILDING PLAN FOR  
**GOLDEN HERITAGE**  
SIGNATURE :-

PLANNER	TITLE- PARKING PLAN TYPICAL PLAN FRONT ELEVATION SECTIONAL VIEW	SH NO-15
---------	---	----------

J.E./INAC	A.E./INAC
SPECIAL OFFICER, INAC	