



BRIEF SPECIFICATION

- STEEL = Fe-500 Grade TMT Steel Shall be used.
- FOUNDATION = CEMENT CONCRETE(1:1.5:3)M20 Grade.
- SUPERSTRUCTURE = BRICK WORK IN CM(1:6)
- FLOORING = 25 MM I.P.S./MARBLE/MOSAIC OVER 3" THICK P.C.C.
- D.P.C. = 25 MM th. D.P.C. IN CEMENT CONCRETE(1:1.5:3)
- PLINTH = 0.15 M TH. R.C.C. BAND ALL ROUND IN M20 CONCRETE
- LINTELS = 0.15 M TH. R.C.C. LINTEL IN M20 GRADE CONCRETE
- WOOD WORK = ALL WOOD WORK IN HARD WOOD.
- PLASTERING = 12mm TH. CEMENT PLASTER BOTH SIDE IN CM (1:6)
- FINISHING = FIRST CLASS APPROVED QUALITY.
- ANTITERMITE = ANTI TERMITE TREATMENT IN FLOOR SHALL BE DONE.
- WATER PROOFING = ROOF AND WALL SHALL BE OF WATER RESISTANT.
- DRAINAGE = ADEQUATE DRAINAGE SHALL BE PROVIDED.
- IS CODES = BUILDING CODE OF INDIA SHALL BE FOLLOWED.
- CEMENT = 53 GRADE PRODUCED FROM 'A' GRADE PLANT.
- WALL = OUTER(0.23 THICK) & INNER(0.12 THICK)

SCHEDULE OF OPENINGS

D =1.00X2.10	D1 =0.90X2.10	D2 =0.75X2.10
W =1.20X1.20	W1 =0.90X1.20	V =0.60X0.45

SCHEDULE OF AREA

GROUND FLOOR	15.01 x 9.80 = 147.10
FIRST FLOOR	15.01 x 9.80 = 147.10
TERRACE FLOOR	15.01 x 9.80 = 147.10

TITLE OF DRAWING

SIGNATURE OF OWNER	SIGNATURE OF ENGINEER
_____	_____