



BRIEF SPECIFICATION
 STEEL = Fe-500 Grade TMT Steel Shall be used.
 FOUNDATION = CEMENT CONCRETE(1:1.5:3)M20 Grade.
 SUPERSTRUCTURE = BRICK WORK IN CM(1:6)
 FLOORING = 1" L.P.S./MARBLE/MOSAIC OVER 3" THICK P.C.C.
 D.P.C. = 1" th. D.P.C. IN CEMENT CONCRETE(1:1.5:3)
 PLINTH = 6" TH. R.C.C. BAND ALL ROUND IN M20 CONCRETE
 LINTELS = 6" TH. R.C.C. LINTEL IN M20 GRADE CONCRETE
 WOOD WORK = ALL WOOD WORK IN HARD WOOD.
 PLASTERING = 12mm TH. CEMENT PLASTER BOTH SIDE IN CM (1:6)
 FINISHING = FIRST CLASS APPROVED QUALITY.
 ANTI TERMITE = ANTI TERMITE TREATMENT IN FLOOR SHALL BE DONE.
 WATER PROOFING = ROOF AND WALL SHALL BE OF WATER RESIS.
 DRAINAGE = ADEQUATE DRAINAGE SHALL BE PROVIDED.
 IS CODES = BUILDING CODE OF INDIA SHALL BE FOLLOWED.
 CEMENT = 53 GRADE PRODUCED FROM 'A' GRADE PLANT.

SCHEDULE OF DOOR & WIN.

SL.	TYPE	SIZE	DESCRIPTION
1	R.S.	8'3"X7'0"	STEEL WORK
2	D	3'3"X7'0"	FULLY PANNEL
3	D1	3'0"X7'0"	SHUTTER
4	D2	2'6"X7'0"	" " "
5	W	4'0"X4'0"	FULLY GLAZED
6	W1	3'0"X4'0"	"
7	v	2'0"X2'0"	GLASS WORK

TITLE OF DRAWING

REVISED RESIDENTIAL BUILDING PLAN FOR SRI YAMUNA PRASAD SINGH S/O- LATE MOTILAL SINGH IN MOUZA- CHAS P.S.- CHAS P.S. NO.-30 DIST- BOKARO (JHARKHAND) UNDER KHATA NO.- 307 PLOT NO.- 171 AREA- 6.03 DECIMAL.

SIGNATURE OF OWNER

SIGNATURE OF ENGINEER

