

STRUCTURAL SAFTY CERTIFICATE

THIS IS SAFTY THAT THE STRUCTURAL DESIGN OF THIS BUILDING IS AS PER IS CODE 1893 - 1884 - & 4326 - 1993 TO MAKE THE SAME EARTH QUAKE RESISTANT.

SPECIFICATION

1. BRICKWOR IN FOUNDATION \$ PLINTH SHALL BE FIRST CLASS BRICK IN CEMENTMORTAR 1:6 AND HALBRICK WILL BE 1:4CEMENT MORTAR
2. MASONRY FOUNDATION WITH ISOLATED R.C.C COLUMN SHALL BE PROVIDED.
3. ROLLING GLAZING/ STRUCTURAL GLAZING OF GOOD QUALITY AND MARK VENTILATOR SYSTEM SHALL BE USED.
4. ROLLING SHUTTERS SHALL BE USED FOR SHOPS OPENING.
5. M.S GLAZED/ANODIZED ALUMINIUM/NCL SECCLOR WINDOW AND R.C.C WITH CEMENT MORTAR 1:4
6. ALL R.C.C WORKS SHALL BE DONE IN 1:2:4 MIX CONCRETE
7. TATA TMT STEEL BARS SHALL BE USED IN RC.C STRUCTURES
8. ALL MASONARY SURFACE SHALL BE PLASTERED WITH CEMENT MORTOR 1:6. OVER R.C.C SLAB /R.C.C
9. ALL STEEL AND WOOD WORK SHALL BE PAINTED WITH SYNTHETIC ENML.PAINT.
10. ALL SANITARY AND ELECTICAL FITTINGS SHALL BE OF STANDARD MAKE AND WORKMENSHIP .
11. KOTTA STONE /MOSAIC FLOORING INCLUDING STAIRCASE SHALL BE USED