



SPECIFICATIONS

- 1) FOUNDATION - R.C.C. COLUMN STRUCTURE
- 2) WALLS - 14 CLASS BRICK WORK IN RED BRICK IN CEMENT MORTAR 1:4
- 3) ALL COLUMN BEAM IN TORR STEEL & 1:1.5:3 CEM. CONCRETE
- 4) FLOORING - 1" L.P.S. 12:4 OVER FLAT BRICK SOLING AND MOSAIC AS PER REQUIREMENT.
- 5) R.C.C. ROOF SLAB 100 MM THK IN M 20
- 6) STAIR WAST SLAB 4" THK, STEPS 300 X 150.
- 7) CHIMNEY 3" THK 0.5% WIDE IN R.C.C. 12:4.
- 8) PLASTER 1/2" THK 1:8 INSIDE & 1/4" OUTSIDE CEILING 1/4" THK IN 1:4.
- 9) WOOD WORK 1 1/2 THK FLUSH DOORS, WINDOWS IN STEEL GLAZED AS PER DESIGN.

DOOR / WINDOW SCHEDULE

S.NO	TYPE	WIDTH	HEIGHT	LINTEL	DESCRIPTION
1	W	100	120	2.10	
2	W	120	120	2.10	
3	W	80	120	2.10	
4	V	80	180	2.10	
5	V	80	180	2.10	
6	D	105	2.10	2.70	
7	DF	80	2.10	2.70	
8	DF	80	2.10	2.70	
9	DF	80	2.10	2.70	
10	DM	100	2.10	2.70	
11	DM	100	2.10	2.70	
12	DM	105	2.10	2.70	
13	DM	105	2.10	2.70	
14	DM	100	2.10	2.70	

FAR CALCULATION

BUILT UP AREA - 2315 SFT  
2315 X 2 = 4630 SFT

SHEET NO.  
1/1



SIGNATURE OF ARCHITECT

SIGNATURE OF OWNER

