



This is certify that the structure design is in accordance with the latest I-S code(I-S 875, I-5456-2002, I-5 1 893-2000) for design & loading conditions (Besmic/wind/dead/live) and other all parameters are taken in account for safety of the structure.

- BRIEF SPACEFICATION**
- BRICK WORK IN FOUNDATION & SUPERSTRUCTURE.
  - FIRST CLASS BRICK WORK IN CEMENT MORTAR (1:6)
  - D.P.C. - " D.P.C. IN CEMENT CONCRETE (1:2:4).
  - FLOOR----- (a) 1" I.P.S. (b) MOSAIC FLOORING.
  - ROOF----- 5" THK. R.C.C. ROOF (1:1.5:3)
  - LINTEL BAND AT 3' LVL -- 6" THK. R.C.C. LINTEL (1:1.5:3)
  - STAIRS RISE-- 6", TREAD-- 10"
  - DOORS D-3'3"X7'0", D1-3'0"X7'0", D2-2'6"X7'0"
  - WINDOWS-----W-5'0"X4'0", W1-4'0"X4'0", W2-2'6"X4'0"
  - VENTS-----2'0"X2'0"
  - SAL WOOD FRAME & PAISAL WOOD SHUTTERS SHALL BE USED FOR DOOR.
  - ALUMNIUM GLAZED WINDOW AND VENTILATORS WITH GUARD BARS SHALL BE USED.
  - I.P.S. FLOOR SHALL BE USED OVER R.C.C. SLAB/P.C.C.
  - ALL MASONRY SURFACES SHALL BE PASTERED WITH CEMENT MORTAR 1:6 R.C.C.WITH CEMENT MORTAR 1:4 IN ROOF
  - ALL STEEL AND WOOD WORK SHALL BE PAINTED WITH SYNTHETIC PANT .
  - ALL SANITARY AND ELECTRICAL FITTINGS SHALL BE OF STANDERD AND COMMERCIAL QUALITY .

**SCHEDULE OF DOORS AND WINDOWS**

Type	Width	Height	Lintel	Description
D	1050	2100	2100	shutter
D1	975	2100	2100	double shutter panel door
D2	900	2100	2100	single shutter panel door
D3	750	2100	2100	single shutter panel door
D4	1800	2100	2100	Fully glazed door
D5	1200	2100	2100	double shutter panel door
W	1200	1200	2100	4 leaf glazed shutter
V	600	600	2100	ventilation

**PROJECT**  
 PROPOSED RESIDENTIAL BUILDING FOR SRJ BINOD PRASAD YADAV S/O LALJEE YADAV

**CLIENT**  
 PROPOSED RESIDENTIAL BUILDING FOR SRJ BINOD PRASAD YADAV S/O LALJEE YADAV, LAND UNDER MOUZA :- HARLATANR, NO:- 264, WARD NO - 03, J.B. NO:- 19 / 11, SETTLEMENT PLOT NO.- 158 & 159, WITHIN MADHUPUR NAGAR PARIASHAD, THANA - MADHUPUR, DISTT- DEOGHAR, JHARKHAND

DESIGNED BY	UJJAWAL KUMAR	sheet
CHECKED BY	NASSIR AHMAD	01
ISSUE ONLY FOR Submission .		

