





- GENERAL SPECIFICATIONS**
- FOUNDATION :** P.C.C. work should be as per design. R.C.C. column footing, Column & its base as per design work should be as per design.
  - SUPERSTRUCTURE :** R.C.C. Column, beam & roof slab as per design should be provided unless as per design of reinforcement should be 100 c/c of bar, study should be provided in roof slab. Required cement mortar for 250mm wall is (1:6) & for (1:4) for 217mm wall. Curing must be done for proper period.
  - INTERNAL FINISHES:** Plaster in rooms, marble/ceramic tile flooring in kitchen & toilet. P.C.C. in internal walls & plaster up to 2.1 roof in walls of toilet & kitchen as per schedule.
  - DOORS & WINDOWS :** Windows when sanitary work is in place. All doors for hot water supply & P.C.C. pipes for cold water supply.
  - ELECTRIFICATION :** All electrical work should be as per design. All wiring in non-hazardous areas. All in low potential for earth system. Proper heavy earthing must be provided.



Sl. NO.	ITEM	DIMENSION	DESCRIPTION
1	D	2.13 X 2.13	Sl wood chankar & Readymade Flush door
2	D1	1.07 X 2.13	Sl wood chankar & Readymade Flush door
3	D2	0.91 X 2.13	Sl wood chankar & Readymade Flush door
4	D3	0.76 X 2.13	Sl wood chankar & Readymade Flush door
5	W	1.22 X 1.22	Fully glazed window
6	WT	0.91 X 1.22	Fully glazed window
7	V	0.61 X 0.61	Ceiling Ventilator



SCALE : 1:100 AS MENTIONED IN DRAWINGS

SIGNATURE OF OWNER

SIGNATURE OF REGISTERED CONSULTANT NAC SERAIKELLA

SIGNATURE OF ENGINEER NAC SERAIKELLA

SIGNATURE OF EXECUTIVE OFFICER NAC SERAIKELLA