

SECTION SCALE 1/50 SEPTIC TANK DETAILS

PLAN FOR SEPTIC TANK

DETAIL OF GROUND WATER RECHARGING PIT WITH SILT TANK SCALE - N.T.S.

PLAN

SECTION

FRONT ELEVATION

SIDE ELEVATION

CROSS - SECTION ON X-X

CROSS - SECTION ON Y-Y

FLOOR PLAN 100

FLOOR PLAN 200

FLOOR PLAN 300

BRIEF SPECIFICATION

- BRICK WORK IN FOUNDATION & SUPERSTRUCTURE.
- FIRST CLASS BRICK WORK IN CEMENT MORTAR (1:2:4)
- D.P.C. - D.P.C. IN CEMENT CONCRETE (1:2:4).
- FLOOR - (a) 1" I.P.S. (b) MOSAIC FLOORING.
- ROOF - 5" THK. R.C.C. ROOF (1:1.5:3)
- LINTEL BAND AT 3' LEVEL - 6" THK. R.C.C. LINTEL (1:1.5:3)
- STAIRS RISE - 6", TREAD - 10"
- DOORS - D-3'3"x7'0", D1-3'0"x7'0", D2-2'6"x7'0"
- WINDOWS - W-5'0"x4'0", W1-4'0"x4'0", W2-2'6"x4'0"
- VENTS - 2'0"x2'0"
- SAL WOOD FRAME & PAISAL WOOD SHUTTERS SHALL BE USED FOR WINDOW.
- ALUMINIUM GLAZED WINDOW AND VENTILATORS WITH GUARD BARS SHALL BE USED.
- I.P.S. FLOOR SHALL BE USED OVER R.C.C. SLAB/P.C.C.
- ALL MASONARY SURFACES SHALL BE PLASTERED WITH CEMENT MORTAR 1:6 R.C.C WITH CEMENT MORTAR 1:4 IN ROOF.
- ALL STEEL AND WOOD WORK SHALL BE PAINTED WITH SYNTHETIC PAINT.
- ALL SANITARY AND ELECTRICAL FITTINGS SHALL BE OF STANDARD AND COMMERCIAL QUALITY.

SCHEDULE OF DOORS AND WINDOWS

S.No	Type	Width	Height	Lintel	Description
1	D	1050	2100	2100	shutter
2	D1	975	2100	2100	double shutter panel door
3	D2	900	2100	2100	single shutter panel door
4	D3	750	2100	2100	single shutter panel door
5	D4	1800	2100	2100	Fully glazed door
6	D5	1200	2100	2100	double shutter panel door
7	W	1200	1200	2100	4 leaf glazed shutter
8	V	600	600	2100	ventilation

CLIENT

PROPOSED RESIDENCIAL BUILDING FOR SMT. ASHA DEVI W/O SRI NARAD PRASAD SINGH, LAND UNDER MOUZA - JHOUNSAGARHI, S.P.NO. - 5, J.B. NO. - 21, 11/3539, THANA- DEOGHAR, NO.- 582, DISTT- DEOGHAR, JHARKHAND.

DESIGNED & CHECKED BY	UJJAWAL KUMAR	sheet
DRAWN	NASSIR AHMAD	01
ISSUE ONLY FOR Submission.		
ARCHITECT	CLIENT	