
SLOPE OF DRAIN=1:200 SECTION OF .075 0.91 SPECIFICATION

B/W IN C.M (1:6).. P.C.C (1:4:8). BRICK SOLLING SAND FILLING


R.C.C (1:1.5:3) COVER SLAB.



FOUNDATION.

읶

DRAIN



兄.C.C COVER SLAB

-B/W IN C.M(1:6)

SPECIFICATION

- 1. D.P.C 1:2:4 +2 / CICO.
- COLUMN &FOOTING R.C.C (1:1.5:3).
- BEAMS, SLAB & LINTEL R.C.C(1:1.5:3:)

 \mathcal{S}

- 4. WALLS: - BRICKWORK IN C.M 1:6
- . U WINDOWS: -FULLY GLAZEDSTEEL CASEMENT.
- DOORS: -35MM TH. FLUSH DOORS
- PLASTER: -1/2" TH. PLASTER ON WALL 1:6
- 8. WALL FINISH : DRY DISTEMPER ON INSIDE SNOWCEM ON OUTSIDE
- 10. WIRING: CONCEALED COPPER WIRING FLOORING: -vitrified/ceramic tiles

Structure Detail

DRAIN

SAND FILLING B.F SOLLING P.C.C(1: 4: 8)